# **CUSTOM SOLUTIONS**

**OEM, CUSTOM BRANDING, CUSTOM KITS AND SOLUTIONS** 

## **SOLUTIONS**

A-M Systems supplies the world's leading brands and OEMs with custom-branded, customconfigured medical devices and equipment.

- Custom-configured PFT kits and breathing circuits
- Custom branding and packaging
- PFT filters with custom port sizes

Contact us to learn more. sales@a-msystems.com






Since 1976, our unwavering commitment to product excellence, competitive prices and customer service has earned us satisfied customers in more than 100 countries.

The Neurophysiology Division designs and The Pulmonary Division designed and developed the manufactures a wide range of scientific instruments, popular VBMax<sup>™</sup> line of pulmonary function test including stimulators, intracellular and extracellular filters and the versatile ViroMax<sup>™</sup> viral-bacterial amplifiers, and patch clamps. Leading universities filter. The Division also answered the growing and research institutions worldwide use our demands worldwide for OEM products by offering instruments and accessories, including electrodes, custom packaging, branding and labeling across insulated wires and capillary tubing, to perform ground-breaking investigations into learning and a wide range of pulmonary and respiratory care memory, Alzheimer's and Parkinson's diseases, and products. models of stroke, deafness and blindness.

We supply some of the world's largest manufacturers and distributors with custom-branded calibration syringes and other pulmonary and respiratory care products. Our PFT kits, which are designed to help clinicians save time, can also be customized to meet specific needs of a hospital or clinic.

The medical devices are manufactured under the strict standards of ISO 13485:2016, FDA Quality









Device Regulations, and Canada Medical Device Regulations (SOR/98-282).

Both A-M Systems Divisions are united by a singular commitment to our customers who challenge us to deliver innovative, high-quality products and services efficiently and affordably.

Learn more about how we can help you. If you like to become a distributor, contact us today!

**PULMONARY & RESPIRATORY CARE** PRODUCTS

A-M Systems is a leading global manufacturer and distributor of high-quality respiratory care products and precision neurophysiology instruments with the goal of making health-care innovation and efficiency affordable.



131 BUSINESS PARK LOOP SEQUIM, WA 98382, U.S.A.









# **VBMAX<sup>™</sup> PFT FILTERS & KITS**

#### FOR SPIROMETRY, BODY PLETHYSMOGRAPHY, PULMONARY FUNCTION TESTING

VBMax<sup>™</sup> PFT Filters combine low flow resistance with high filtration efficiency to help protect the patient and equipment during lung function tests.

- Bacterial filtration efficiency: > 99.999%
- Viral filtration efficiency: > 99.99%
- Resistance to flow:
- 0.75 cm H<sub>2</sub>O L•sec<sup>-1</sup> @ 14 L•sec<sup>-1</sup>
- 0.66 cm H<sub>2</sub>O L•sec<sup>-1</sup> @ 12 L•sec<sup>-1</sup>
- Exceeds ATS and ERS standards<sup>1</sup>
- Membrane protects electrostatic filter media
- Effective dead space: 45 mL
- For single-patient, single use only
- Free of latex, PVC, DEHP, BPA
- Fits most PFT equipment in use today
- Custom sizes available to fit your designs



**VBMAX<sup>™</sup> S-SERIES** 

Smaller mouthpiece with ridges for pediatric use or for adults with smaller aperture.



**VBMAX<sup>™</sup> E-SERIES** 

**Oval-shaped mouthpiece with** optional, disposable rubber mouthpiece.



VBMAX<sup>™</sup> STANDARD

Straight ports with a paper mouthpiece or an optional pediatric adapter.

VBMAX<sup>™</sup> PFT KITS

**STANDARD** 

& CUSTOM

PFT KITS

SAVE TIME

**REDUCE RISKS** 

Standard and custom PFT kits that are individually packaged to save time and reduce risks.

#### NOSE CLIPS

Foam and rubber nose clips in standard (white) and large (blue) sizes.

# **CALIBRATION SYRINGE**

FOR ATS/ERS-RECOMMENDED DAILY CHECKS OF PULMONARY FUNCTION ANALYZERS



- 3.0 liter capacity
- ±0.25% accuracy
- Fits all PFT equipment
- Rubber feet prevent rolling
- One-year warranty
- Repair service available
- Annual recalibration required
- Custom colors and logos available

## **CALIBRATION REQUIREMENTS**

ATS and ERS standards require daily checks of spirometers and other PFT equipment using a 3-Liter calibration syringe to ensure accuracy of test results.<sup>1</sup>

A-M Systems syringes offer a low-cost method for checking

# VIROMAX<sup>™</sup> IN-LINE BVF

#### **BIDIRECTIONAL BACTERIAL-VIRAL FILTER FOR IN-LINE USE**

Choose from any of our prepackaged PFT Kits or ask us about custom kits using any combination of:

- VBMAX<sup>™</sup> Standard, E-Series, or **S-Series**
- Paper and/or Rubber Mouthpiece
- Standard and Large, Rubber and Foam Nose Clips

**RUBBER MOUTHPIECE** 

Disposable rubber mouthpieces

fit VBMax<sup>™</sup> Standard, E-Series,

and S-Series.



- Bacterial filtration efficiency: > 99.999%
- Viral filtration efficiency: > 99.99%
- Flow resistance: 1.5 cm H<sub>2</sub>O @ 60 L•min<sup>-1</sup>
- Low effective dead space: 45 mL
- Electrostatic media in protective membranes
- ISO 5356 Connectors: 15F/22M, 15M/22F
- Bidirectional airflow
- Disposable, for single-patient use only
- Free of latex, PVC, DEHP, BPA
- Transparent housing for visual inspection

# **HYDROMAX<sup>™</sup> HME FILTER**

FOR PASSIVE HUMIDIFICATION IN ANESTHESIA AND INTENSIVE CARE

- Combined HME and bacterial-viral filter
- Helps reduce risk of colonization
- Hygroscopic membrane traps moisture
- Minimal resistance and pressure drop
- Supplied clean and individually bagged
- Single-patient, single-session use
- Free of latex, PVC, DEHP, BPA
- Available in custom-configured circuits

### HYDROMAX SPECIFICATIONS

| FILTRATION EFFICIENCY <sup>1</sup> |             | PRESSURE DROP/RESISTANCE <sup>2</sup> |                         |
|------------------------------------|-------------|---------------------------------------|-------------------------|
| Bacterial                          | > 99.9999%  | 30 L/min                              | 0.8 cm H <sub>2</sub> O |
| Viral                              | > 99.99%    | 60 L/min                              | 1.9 cm H <sub>2</sub> O |
|                                    |             | 90 L/min                              | 3.3 cm H <sub>2</sub> O |
| MOISTURE OUTPUT                    |             |                                       |                         |
| V <sub>τ</sub> 250 mL              | 37.2 mg/L   | Dead space                            | 56 mL                   |
| V <sub>τ</sub> 500 mL              | 36.9 mg/L   | Weight                                | 21 g                    |
| $V_{T}$ 750 mL                     | 35.4 mg/L   |                                       |                         |
| V <sub>T</sub> 1000 mL             | 36.6 mg/L   | CONNECTORS                            |                         |
|                                    |             | Patient Side                          | 15F/22M                 |
| Tidal Volume Range                 | 250-1000 mL | Machine Side                          | 15M/22F                 |
|                                    |             |                                       |                         |

1. Tested by Nelson Laboratories Inc., U.S.A.

- 2. Tested according to ISO 9360-1:2009.
- 3. Conforms to Regulation (EU) 2017/745 on medical devices.

- the volume of PFT equipment.
- Annual recalibration of the 3L syringe is recommended to ensure consistent and optimal performance.
- 1. Eur Respir J 2005; 26: 319-338

### **QUALITY**

A-M Systems strictly adheres to and manufactures products under the standards of:

- ISO 13485:2016
- FDA Quality System Regulations
- EU Medical Device Regulations Canada Medical Device
- Regulations

